

SKU	SKU Type	SKU Description	H/M	List Price
Scanning - HH - Hand-Held Scanners: General Purpose Area Imaging - 4600g				
Hardware - Kit				
4600GSFH051C-0F00E	Standard	4600g USB Kit: imager (4600GSF051CE), disinfectant-ready housing, straight USB cable (42206161-01E), and 2D Quick Start Guide	H	£341
Hardware - Imager Kits: 4600gSR				
4600GSR051C-0A00E	Standard	4600g KBW Kit: imager (4600GSR051CE), coiled KBW cable (42206132-02E), and 2D Quick Start Guide	H	£311
4600GSR051C-0F00E	Stocking	4600g USB Kit: imager (4600GSR051CE), straight USB cable (42206161-01E), and 2D Quick Start Guide	H	£311
4600GSR051C-0G00E	Standard	4600g User's Guide Kit: imager (4600GSR051CE) and User's Guide (CD)	H	£303
Hardware - Imager Kits: 4600gSF				
4600GSF051C-0A00E	Standard	4600g KBW Kit: imager (4600GSF051CE), coiled KBW cable (42206132-02E), and 2D Quick Start Guide	H	£311
4600GSF051C-0F00E	Stocking	4600g USB Kit: imager (4600GSF051CE), straight USB cable (42206161-01E), and 2D Quick Start Guide	H	£311
4600GSF051C-0G00E	Stocking	4600g User's Guide Kit: imager (4600GSF051CE) and User's Guide (CD)	H	£303
Hardware - Imager Kits: 4600gHD				
4600GHD051C-0F00E	Standard	4600gHD USB Kit: Imager (4600GHD051CE), straight USB cable (42206161-01E), and 2D Quick Start Guide	H	£326
4600GHDH051C-0F00E	Stocking	4600gHD with disinfectant-ready housing, straight USB cable and Quick Start Guide	H	£356
Hardware - Imager: 4600gSR (General Purpose) Interfaces / Housing Color / Aimer				
4600GSR031CE	Standard	Supports true RS-232 and 12V DEC wedge / Gray / Green LED	H	£303
4600GSR051CE	Standard	Supports TTL RS-232, USB, KBW, IBM 4683, and Wand Emulation / Gray / Green LED	H	£303
4600GSR151CE	Standard	Supports TTL RS-232, USB, KBW, IBM 4683, and Wand Emulation / Black / Green LED	H	£303
Hardware - Imager: 4600gSF (General Purpose)				

4600GSF031CE	Standard	Supports true RS-232 and 12V DEC wedge / Gray / Green LED	H	£303
4600GSF051CE	Standard	Supports TTL RS-232, USB, KBW, IBM 4683, and Wand Emulation / Gray / Green LED	H	£303
4600GSF151CE	Standard	Supports TTL RS-232, USB, KBW, IBM 4683, and Wand Emulation / Black / Green LED	H	£303
Hardware - Imager: 4600gHD				
4600GHD051CE	Standard	Supports TTL, RS-232, USB, KBW, and IBM4683 / Gray / Green LED	H	£318
4600GHD151CE	Standard	Supports TTL, RS-232, USB, KBW, and IBM4683 / Black / Green LED	H	£318
4600GHDH051C	Standard	Supports TTL, RS-232, USB, KBW and IBM4683 / White Disinfectant-Ready Housing / Green LED	H	£348
Accessories - Power				
77900507E	Stocking	UK power cord, used to connect power supply to AC outlet V Length: 6.0 ft. (1.8m)	H	£6
77900508E	Stocking	European power cord, used to connect power supply to AC outlet V Length: 6.0 ft. (1.8m)	H	£8
PS-050-2400D1-EU	Stocking	5 volt DC power supply, input voltage 100-240v @ 47-63Hz, with EU AC connection (77900508E)	H	£20
PS-050-2400D1-UK	Stocking	5 volt DC power supply, input voltage 100-240v @47-63Hz, with UK AC connection (77900507E)	H	£20
Accessories - Cables				
42203758-03E	Standard	Cable, RS-232 TTL, Connector: D 9 Pin F, power on pin 9, TX data on pin 2, coiled Length: 7.7ft. (2.3m)	H	£28
42203758-03SE	Standard	Cable, RS-232 TTL, Connector: D 9 Pin F, power on pin 9, TX data on pin 2, straight Length: 7.7ft. (2.3m)	H	£9
42203758-04E	Stocking	Cable, RS-232 TTL, Connector: D 9 Pin F connector, TX data on pin 2, external power, coiled Length: 7.7ft. (2.3m)	H	£26
42205155-05E	Standard	Cable, IBM 4683/4684/4693/4694 Port 9A/B Length: 10.2 ft. (3.1m)	H	£21
42205895-01E	Standard	Cable, coiled RS-232 TTL, power from PS-2 keyboard/mouse port Length: 7.7 ft. (2.3m)	H	£30
42206132-02E	Stocking	Cable, AT - PS/2 & compatibles, wedge Connector: Mini Din 6 PIN M/F Length: 9.2 ft. (2.8m)	H	£12

42206132-02SE	Stocking	Cable, AT - PS/2 & compatibles, wedge Connector: Mini Din 6 PIN M/F Length: 9.2 ft. (2.8m)	H	£9
42206161-01E	Stocking	Cable, straight Commercial USB Connector: USB Type A Length: 8.5 ft. (2.6m)	H	£12
42206202-02E	Standard	Cable, coiled Commercial USB A Connector: USB Type A Length: 9.2 ft. (2.8m)	H	£30
42206202-03E	Standard	Cable, USB, Retail Length: 12 ft. (3.7m)	H	£42
42206422-01E	Standard	Cable, straight RS-232 TTL, EP, TX Data on Pin 2 Connector: D 9 PIN F Length: 7.7 ft. (2.3m)	H	£15
Accessories - Stands/Holders/Cordless Bases				
HFSTAND5E	Standard	Flex neck holder for hands-free operation/presentation scanning (for 3800r, 3800i, 4600g, 4600r, and 4800i)	H	£15
IMAGESTANDPE	Standard	ImageStand with mounting plate for 4600g	H	£78
IMAGESTANDTE	Standard	ImageStand with countertop decal template for 4600g	H	£71
UCOVERE	Standard	Padded fabric boot cover with hanging ring for 3800r and 4600g	H	£15
UHOLDERE	Standard	Desktop holder for 3800r, 3800i, 4600g, and 4800i	H	£6
Accessories - Documentation				
46GR-48I-UG	Standard	User's Guide (hard copy) for 4600g, 4600r, and 4800i	H	£9
46GR-48IUG-CD	Standard	User's Guide (CD) for 4600g, 4600r, and 4800i	H	£11
Global Services - Service Contracts (Price if service purchased within 30 days of product shipment. Price is per unit per year, except for packages noted as 3 year or 5 year - those are per unit for the				
SVC4600G/R-SMS5	Standard	4600g/4600r, SMS 1-day turnaround, comprehensive coverage, 5-Year	H	£41
Global Services - Post Sale Service Contracts (Price if service purchased during warranty, but 30+ days after product shipment. Price is per unit per year, except for packages noted as 3 year or 5 year, those are per unit for the term.)				
E-SVC4600G/R-S	Standard	4600g/4600r Extended Warranty, 1-Year, Post Sale	H	£22

PRICE DISPLAYED IS THE RRP FROM THE VENDOR

PRICES VALID FROM 25/05/10 UNTIL FURTHER NOTICE BUT ARE SUBJECT TO CHANGE

PLEASE CONTACT US FOR YOUR DISCOUNTED PRICE

info@2dbarcodescanners.co.uk

01785 226855