

3380879

WDT3200

PORTABLE DATA TERMINAL



Big Business Tools. Small Business Attitude.

SPECIFICATIONS

SYSTEM	Microsoft Windows CE 5.0 Core Intel PXA255 Processor @ 300 MHz 64MB SDRAM 64MB Flash ROM Supports SD/MMC Memory Card up to 1GB
DISPLAY	QVGA 240 x 320 color 2.7" TFT LCD display with touch screen and backlight
KEYPAD	36-key keypad with numeric key, alpha key and function key, ESC, ENT, backspace, cursor key, trigger key and other symbol key
INPUT DEVICE	Keypad, touch screen, full alphanumeric software keyboard and laser barcode scanner
SYMBOLOGIES	UPC-A/E, EAN-8/13, Codabar, Code 39 (3 of 9), Code 39 (3 of 9) full ASCII, Code 93, Code 32, Interleaved & Standard 2 of 5, EAN 128, Code 11, Delta, MSI/Plessey, Code 128, Toshiba
ENCLOSURE	Dimension 199.5mm(L)x72.1mm(W)x39.6mm(H) Weighs 360g with battery pack
ENVIRONMENT	Operating Temp 32°F to 122°F (0°C to 50°C) Storage Temp -4°F to 158°F (-20°C to 70°C) Relative Humidity 5% to 95% (non-condensing) IP Rating 54
ELECTRICAL	Sources: 1.) 100-240V 5V/3A DC external adapter 2.) Rechargeable Li-Ion battery pack @ 3.7V 1950mAh 3.) Rechargeable Backup battery @ 3.7V 120mAh Standby consumption: 90-100 mA Suspend consumption: 2-5 mA Battery life is more than 12 hours at 1 scan 1 pass via BT per 5 seconds Charging via charging cable or optional docking station is 4 hours
PART NUMBERS	WDT3200 Portable Data Terminal (without pistol grip): 633808920289 WDT3200 Portable Data Terminal (with pistol grip): 633808920296 WDT3250 Portable Data Terminal (with pistol grip), 802.11 b/g: 633808920388 Pistol grip: 633808121389 Docking cradle with USB cable: 633808920333